



Areas of application: **See over**

Simpler version of Helico goggles, with colourless soft PVC body (cadmium free) and four ventilation openings. Can be worn over any type of prescription glasses. The elastic headband is easy to adjust.

Just choose the type of lens that best suits your way of working.

Variantes

0156 0000 xx PF with clear polycarbonate lens
 0157 0000 xx HF with clear anti-fog acetate lens, hyclear

Packaging as per price list

Spare parts:

9921 2060 00 PF clear polycarbonate lens
 9921 2080 00 HF clear anti-fog acetate lens, hyclear

Packing units

in polybag	1 pc		
Dispatch unit (VS)	200pcs	in cardboard box 800x405x410	19 kg
Palett 9 x VS	1800 pcs		194 kg
in individual box	1 pc		
Dispatch unit (VS)	100 pcs	in cardboard box 790x580x580	25 kg
Palett 4 x VS	800 pcs		130 kg

Fields of application

	PF	HF
Water	■	■
Methanol	▲	▲
Ethanol		■
Ethyl acetate		▲
Methylene chloride		▲
Acetone	▲	■
Carbon tetrachloride	▲	■
Trichlorethylene	▲	▲
Tetrachlorethylene	▲	▲
Benzene	▲	▲
Xylene		■
Petroleum ether	▲	■
Paraffin	▲	▲
Formic acid (conc.)		●
Linseed oil	▲	▲
Turpentine oil	▲	▲
Lavender oil	▲	▲
Ether	▲	▲
Formaldehyde		▲
2 chlorophenol		▲
Acetic 99%		▲
Sulphuric acid (conc.)	●	●
Sulphuric acid 10%	▲	▲
Nitric acid (conc.)	●	●
Nitric acid 10%		▲
Hydrochloric acid (conc.)	●	▲
Hydrochloric acid 10%	▲	▲
Caustic soda (30%)	▲	▲
Citric acid (conc.)		■

Lens resistance; the eyes remain protected in any case.

Test procedure

The samples were subjected to the action of solvent for 30 minutes. The samples were then rinsed under hand-hot running water for one minute, and then dried.

This list of resistance data includes reference values that may be updated by user's own tests. They are based on current levels of experience and knowledge. No legally binding recommendation, either actual or implied, can be inferred from our data with respect to suitability for any particular use or application

■ Constant resistance, optical quality of the sample remains unchanged

▲ Short-term resistance, optical quality slightly affected

● Low resistance, optical quality rendered insufficient

Standards' compliance

Standard of reference	DIN EN 166
Protection level	Mechanical risks, visual radiation
Use area	Basic use according to EN 166 . All lenses are optical class 1 according to EN 166 and suitable for all day use.
Notified body	DIN CERTCO 0196

All specifications and illustrations in this data sheet are non-binding. The manufacturer reserves the right to change the specifications for manufacturing or sales technical reasons. BST / 14. Februar 2008

