



Areas of application: **See over**

The dark option. Welding spectacles in a classic and robust design that stand out through their functionality. Two available temple versions allow an easy adaptation to any head size.

Variantes

0330 0000 xx EG* with green welding lenses EG and standard temples

0335 0000 xx EG* green welding lenses EG with hook-type temples

*Please state the required shade in each case
EG shades 4-6 (other shades on request)

Packaging as per price list

Colours

All Uniweld goggles are supplied in **ANTHRAZIT**, unless otherwise indicated. Also available in **BLACK**, **GREY** or **BEIGE**. Alternative colours must be clearly indicated next to the article number on each order.

Spare parts

9921 4100 00 EG 1 pair green welding lenses EG, shades 4-6

Packing units

			EG
in polybag	1 pc		
Packing unit (VE)	50 pcs	in cardboard box 410x270x200	2.5 kg
Dispatch unit (VS)	300 pcs	in cardboard box 800x405x410	15 kg
Palett 9 x VS	2700 pcs		157 kg

Fields of application of the welder's goggles

Protection shade	Application	Gases	Volume throughput l/h
2	Light flame-cutting work		
3	Light flame-cutting work		
4	Welding and brazing	Acetylene	to 70
	Cutting	Oxygen	to 900
5	Welding and brazing	Acetylene	over 70 to 200
	Cutting	Oxygen	over 900 to 2000
6	Welding and brazing	Acetylene	over 200 to 800
	Cutting	Oxygen	over 2000 to 4000
7	Welding and brazing	Acetylene	over 800
	Cutting	Oxygen	over 4000 to 8000
8	Cutting	Oxygen	over 8000

Shades over 8 are not suitable due to lack of protection for the face..

Technical data for the clear lenses

	EG
EG protection shades	2-8
Material	Glass
Safety lens	no
Marking	Inner side

All lenses are optical class 1 according to EN 166 and suitable for all day use.

Standards' compliance

Standard of reference:	DIN EN 166	
Protection level	frame	Mechanical risks, visual radiation
	Lenses EG	welding filter
Use area	Basic use according to DIN EN 169	
Notified body	DIN CERTCO 0196	

All specifications and illustrations in this data sheet are non-binding. The manufacturer reserves the right to change the specifications for manufacturing or sales technical reasons. BST / 14. Februar 2008

